



ROCK **PICKERS**

REMOVE YOUR ROCKS.

Rite Way rock pickers with hydraulically driven reels can be used as both a fork-type and rotary rock picker for the ultimate in flexibility and efficiency. The reels rapidly pick small to medium sized stones or can be used as a support while picking large rocks.



ROCKPICKER FEATURES

1 - Hydraulic Drive.

Match the reel bat speed to your picking needs, stop the reel to pick a single large rock, or clear a jammed rock by reversing the reel.

2 - Wide range of rake heights.

Adjust rake height and use bats for support to pick large rocks and load them into the hopper. Or, keep rake at a minimal angle to separate rocks from dirt quickly and with minimal ground disturbance.

3 - Shock protection.

Both reels and forks are shock-protected to allow our rockpickers to remove extralarge rocks. The small but mighty RR250ST picks rocks up to 24" x 45" (61 x 144 cm) and the RR900ST handles rocks up to 28" x 55" (81 x 140 cm).

4 - Simple to dump rocks.

An electric solenoid lets you unload with the flick of a switch from your tractor.

5 - Ready to Move.

The Hydraulic angled hitch allows you to go from transport to field mode and back again quickly and easily.

REEL 8 FORK TEAM UP

FOR PICKING LARGE ROCKS.



By positioning the rake and using the reels as a support, the RR250ST can pick rocks up to $24" \times 45" (61 \times 144 \text{ cm})$ and the RR900ST picks rocks up to 28" x 55" (81 x 140 cm).

ROCKPICKER STANDARD EQUIPMENT:

- Multi-position Hydraulic Swing Hitch
- 10" Side Wind Parking
- Safety chains

8.7' / 2.7 m Transport Width



RR250ST 1.25 CU YD / 1 CU M CAPACITY

3.2 CU YD/ 3.2 CU M CAPACITY 10.8' / 3.3 m Transport Width

RR900ST



RAKE YOUR ROCKS.

Clean up your field in record time when you use a Rite Way Windrower in conjuntion with your rockpicker.

WINDROWER FEATURES

Affordable and efficient.

An affordable way to speed up your rock picking. Handles rocks from 1 1/2" to 12" (4 to 30 cm) diameter.

Three-row spiral design.

For improved speed and efficiency of delivering rocks to

Replaceable Hard-surface teeth.

Ensures long life of the equipment.

Hydraulic drive.

Hydraulics control both the depth of the rake and the field to transport positions.

Seedbed preparation.

Efficiently breaks up clumps and prepares the soil for seeding.

Working width: 142" (3 1/2 m)

WINDROWER STANDARD EQUIPMENT:

• Replaceable hard surface







MADE TO WORK. BUILT TO LAST.

Whether your rocks are small or large, the Rite Way Rock Pickers and Windrower are ideal to prepare your land for what's to come. Choose the right size of field-proven equipment to fit your unique needs.

SPECIFICATIONS:

| RR <i>250</i> ST | |
|--------------------------|--|
| DRIVE | Variable Hydraulic Drive |
| REEL | 2 Bat |
| REEL CHAIN | #80 |
| WEIGHT | 2,931 lbs / 1,330 kg |
| PICKING WIDTH | 50" / 127 cm |
| MINIMUM ROCK DIAMETER | 2" / 5 cm |
| MAXIMUM ROCK DIAMETER | 24" x 45" / 61 cm x 114 cm |
| BUCKET CAPACITY | 1.25 cu yd / 0.96 cu meter |
| REEL & BUCKET CONTROL | Electric over Hydraulic |
| WEIGHT CAPACITY | 3,600 lbs / 1,650 kg |
| DUMPING HEIGHT | 38" / 0.97 m |
| TIRES | 12.5L x 15-6 ply |
| нітсн | Multi-Position, Hydraulic Swing |
| HYDRAULIC REQUIREMENTS | 12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar |

| RW1200HD | |
|---------------------------|--|
| WORKING WIDTH | 11' 10" / 3.6 m |
| HEIGHT | 32" / 81 cm |
| WEIGHT | 1,350 lbs / 612.4 kg |
| DRIVE | Hydraulic |
| TRANSPORT HEIGHT | 42" / 1.07 m |
| TRANSPORT LENGTH | 8' 11" / 2.7 m |
| TRANSPORT WIDTH | 12' 3" / 3.7 m |
| HYDRAULIC REQUIREMENTS | 12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar |

| RR900ST | |
|--------------------------|--|
| DRIVE | Variable Hydraulic Drive |
| REEL | 3 Bat |
| REEL CHAIN | #80 |
| WEIGHT | 4,784 lbs / 2,170 kg |
| PICKING WIDTH | 60" / 152 cm |
| MINIMUM ROCK DIAMETER | 2" / 5 cm |
| MAXIMUM ROCK DIAMETER | 28" x 55" / 81 cm x 140 cm |
| BUCKET CAPACITY | 3.2 cu yd / 2.4 cu meter |
| REEL & BUCKET CONTROL | Electric over Hydraulic |
| WEIGHT CAPACITY | 8,000 lbs / 4,500 kg |
| DUMPING HEIGHT | 56" / 1.42 m |
| TIRES | 16.5L x 16.1-6 ply |
| нітсн | Multi-Position, Hydraulic Swing |
| HYDRAULIC REQUIREMENTS | 12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar |

We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the Rock Pickers, Windrower or other land improvement equipment, visit your local Rite Way equipment dealer, or visit www.RiteWayMfg.com

