

## DELUXE FINISHING MOWERS



### GS Models

- New heavier model
- 540 RPM PTO
- Flexible floating hitch
- Greasable Wheel bearings
- Rear Safety chains
- 4 height adjustable wheels



### HDG Models

- 4 height adjustable wheels
- Heavy duty gearbox
- Belt drive
- Chain guard
- 3" wide x 10" diameter solid rubber tires
- Floating hitch
- Single piece formed deck
- Easy access grease points
- Heavy duty cast iron housing with permanent greased ball bearing

### BE-FM48RDGS

### BE-FM60RDGS

### BE-FM72RDGS

### BE-FM84RDHDG

| BLADES         | 3                  | 3                  | 3                  | 3                      |
|----------------|--------------------|--------------------|--------------------|------------------------|
| CATEGORY       | CAT 1              | CAT 1              | CAT 1              | CAT 1                  |
| HP RATING      | 15 HP              | 20 HP              | 30 HP              | 75 HP                  |
| CUTTING HEIGHT | 5" MAX, 1-3/4" MIN | 5" MAX, 1-3/4" MIN | 5" MAX, 1-3/4" MIN | 4-3/4" MAX, 1-3/4" MIN |
| WEIGHT         | 355 LBS            | 410 LBS            | 520 LBS            | 728 LBS                |
| WIDTH          | 48"                | 60"                | 72"                | 84"                    |
| PRICE          | \$2,705            | \$2,904            | \$3,423            | \$5,121                |

## HEAVY DUTY ROUGH CUT MOWERS



- Adjustable cutting height
- Flexible floating hitch
- 540 RPM Slip Clutch PTO
- Heavy duty laminated tail wheel
- Heavy duty deck and side beams
- Rear safety chain
- 2 underside blades with stump protection
- 70 HP gearbox

### BE-RC5HDG

### BE-RC6HDG

### BE-RC7HDG

| BLADES              | 2                            | 2                            | 2           |
|---------------------|------------------------------|------------------------------|-------------|
| CATEGORY            | CAT 1                        | CAT 1                        | CAT 1       |
| DECK WIDTH          | 60"                          | 72"                          | 84"         |
| WEIGHT              | 700 LBS                      | 840 LBS                      | 1,365 LBS   |
| HITCH               | CAT 1 Quick Hitch Compatible | CAT 1 Quick Hitch Compatible | CAT 2       |
| SIDE DECK THICKNESS | 3.5 MM                       | 4 MM                         | 4 MM        |
| TOP DECK THICKNESS  | 3.5 MM                       | 4 MM                         | 5 MM        |
| HP RATING           | Up to 70 HP                  | Up to 70 HP                  | Up to 70 HP |
| PRICE               | \$3,665                      | \$3,976                      | \$5,859     |

## ROTARY TILLERS



- 540 RPM PTO
- Fixed Center Mount Hitch
- Gear Drive
- 6 C-Shaped Tines per Flange
- Parking Stand
- Skid Shoes for Depth Control
- 6-1/2" Tillage Depth

### BE-TS140

### BE-TS160

### BE-TS180

| BLADES        | 42         | 54         | 54         |
|---------------|------------|------------|------------|
| CATEGORY      | CAT 1      | CAT 1      | CAT 1      |
| TILLING WIDTH | 55"        | 63"        | 71"        |
| WEIGHT        | 538 LBS    | 602 LBS    | 643 LBS    |
| HP RATING     | 20 - 50 HP | 20 - 50 HP | 20 - 50 HP |
| PRICE         | \$3,513    | \$3,594    | \$3,853    |

## TPH FERTILIZER SPREADER



- Cat 1, 3PT hitch
- Heavy duty poly hopper
- Stainless steel insert
- Bottom drop spinner
- Manual controls
- Three spread patterns
- 540 RPM PTO

### BE-PFS500G

| CAPACITY | 1,160 LBS |
|----------|-----------|
| WEIGHT   | 140 LBS   |
| PRICE    | \$1,451   |

### BE-PFS250G

| CAPACITY | 550 LBS |
|----------|---------|
| WEIGHT   | 120 LBS |
| PRICE    | \$1,290 |

## TOW BEHIND FERT. SPREADER



### MFS350T

| CAPACITY | 350 LBS |
|----------|---------|
| PRICE    | \$933   |

- Pneumatic tire 14"/600-6
- Steel square hopper
- Spreads seed, fertilizer, sand & salt
- Adjustable towbar with 2" ball hitch
- Heavy duty cast iron, oil bath gearbox



- Includes Hopper Cover
- Clevis Hitch
- 14" Large pneumatic tires

### PFS105T

| CAPACITY | 250 LBS |
|----------|---------|
| PRICE    | \$415   |

## PALLET FORKS

### LIGHT/COMPACT DUTY



**BE-PFLD36EBO**

|             |                                                                            |
|-------------|----------------------------------------------------------------------------|
| FORKS       | 36"                                                                        |
| CAPACITY    | 1,100 LBS                                                                  |
| MOUNTING    | Skid Steer quick-attach for universal compatibility with compact carriages |
| BUILD       | Reinforced steel                                                           |
| APPLICATION | Ideal for landscape nurseries, greenhouses, and estate maintenance         |
| PRICE       | <b>\$741</b>                                                               |

### STANDARD SKID STEER PALLET FORKS



**BE-PF30S42LBO**



**BE-PF5048HBO500J**

**BE-HD5548BO500**

|               |                                                            |                                                            |                                                            |
|---------------|------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------|
| FORKS         | 42"                                                        | 48"                                                        | 48"                                                        |
| CAPACITY      | 2,200 LBS                                                  | 4,400 LBS                                                  | 5,500 LBS                                                  |
| MOUNTING      | Universal Skid Steer mount                                 | Universal Skid Steer mount                                 | Universal Skid Steer mount                                 |
| INFINITE ADJ. | Sliding tines can be locked in any position along carriage | Sliding tines can be locked in any position along carriage | Sliding tines can be locked in any position along carriage |
| TINES         | 1-1/2" X 5" Class II solid hook-type forged steel forks    | 1-1/2" X 5" Class II solid hook-type forged steel forks    | 1-1/2" X 5" Class II solid hook-type forged steel forks    |
| CARRIAGE      | Extra-wide 50" locking                                     | Extra-wide 50" locking                                     | Extra-wide 50" locking                                     |
| PRICE         | <b>\$925</b>                                               | <b>\$1,244</b>                                             | <b>\$1,325</b>                                             |

## SNOW BLOWERS



ASK US ABOUT:

**OPTIONAL HYDRAULIC CHUTE KIT \$1,014**  
SBSNHYDKIT

**BE-SBS5054G**

**BE-SBS6064G**

**BE-SBS7276G**

**BE-SBS8488G**

|                        |                                                                  |                                                                  |                                                                 |                                                                 |
|------------------------|------------------------------------------------------------------|------------------------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------|
| WIDTH                  | 50" - 54"                                                        | 60" - 64"                                                        | 72" - 76"                                                       | 84" - 88"                                                       |
| HITCH COMPATIBILITY    | Cat 1, 3 PT hitch                                                | Cat 1, 3 PT hitch                                                | Category 1, 3 PT hitches                                        | Category 1, 3 PT hitches                                        |
| DRIVE SYSTEM           | 540 RPM PTO with a 6-spline input                                | 540 RPM PTO with a 6-spline input                                | 540 RPM PTO with a 6-spline input                               | 540 RPM PTO with a 6-spline input                               |
| HD BUILD               | 1/4 inch steel gauge                                             | 1/4 inch steel gauge                                             | 1/4 inch steel gauge                                            | 1/4 inch steel gauge                                            |
| AUGER ASSEMBLY         | 14-inch chain-driven auger with integrated shearbolt protection  | 14-inch chain-driven auger with integrated shearbolt protection  | 14-inch chain-driven auger with integrated shearbolt protection | 14-inch chain-driven auger with integrated shearbolt protection |
| DISCHARGE CONTROL      | Manual 340-degree worm gear chute                                | Manual 340-degree worm gear chute                                | Manual 340-degree worm gear chute                               | Manual 340-degree worm gear chute                               |
| ADJUSTABLE DEFLECTOR   | Manual adjustable deflector spout                                | Manual adjustable deflector spout                                | Manual adjustable deflector spout                               | Manual adjustable deflector spout                               |
| HIGH-CAPACITY IMPELLER | 24-inch impeller with 5-inch paddles                             | 24-inch impeller with 5-inch paddles                             | 24-inch impeller with 5-inch paddles                            | 24-inch impeller with 5-inch paddles                            |
| TERRAIN MANAGEMENT     | Heavy-duty adjustable skid shoes to manage clearing height       | Heavy-duty adjustable skid shoes to manage clearing height       | Heavy-duty adjustable skid shoes to protect surfaces and edges  | Heavy-duty adjustable skid shoes to protect surfaces and edges  |
| SERVICEABILITY         | Removable hitch for simplified maintenance and storage solutions | Removable hitch for simplified maintenance and storage solutions | Removable hitch design for simplified storage and repair access | Removable hitch design for simplified storage and repair access |
| PERF. SPECS            | Engineered for tractors ranging from 16 to 35 HP                 | Specifically designed for tractors ranging from 25 to 40 HP      | Rated for 35-60 HP tractors with a 600 lb operating weight      |                                                                 |
| PRICE                  | <b>\$3,984</b>                                                   | <b>\$4,249</b>                                                   | <b>\$4,500</b>                                                  | <b>\$5,157</b>                                                  |